```
1
     DERWENT-ACC-NO:
                       1993-317729
  2
     DERWENT-WEEK: 199340
  3
      COPYRIGHT 1999 DERWENT INFORMATION LTD
  4
  5
     TITLE: Adhesive compsn. for labelling recyclable bottles
     etc. - comprising emulsion of EVA or poly(meth)acrylate,
 6
     and water-insol. cpd. that swells or dissolves in alkali
 7
 8
 9
     PATENT-ASSIGNEE: KURARAY CO LTD[KURS]
 10
 11
     PRIORITY-DATA: 1992JP-0070421 (February 19, 1992)
12
13
     PATENT-FAMILY:
14
     PUB-NO
                          PUB-DATE
                                                     LANGUAGE
15
     PAGES MAIN-IPC
16
     JP 05230427 A
                         September 7, 1993
                                                     N/A
17
     005
                C09J 123/08
18
19
     APPLICATION-DATA:
20
    PUB-NO
                        APPL-DESCRIPTOR
                                                 APPL-NO
21
     APPL-DATE
22
     JP05230427A
                         N/A
                                                   1992JP-0070421
23
     February 19, 1992
24
25
     INT-CL (IPC): C09J123/08; C09J131/02; C09J133/08;
26
     C09J201/06;
27
     G09F003/10
28
29
     ABSTRACTED-PUB-NO: JP05230427A
30
     BASIC-ABSTRACT: An adhesive compsn. for labelling consists
31
     of ethylene/vinyl acetate copolymer emulsions (A1) and/or
     poly(meth)acrylate emulsions (A2); and water-insoluble and
32
33
     alkali-soluble or alkali-swellable cpd. (B).
34
35
     The adhesive compsn. e.g contains filler to improve
     flowability and initial adhesion, and water-soluble resins
36
37
     e.g. polyacrylate and polyester; thickener; tackifier etc.
38
     and has a solids content pref. 20-60 (30-50) wt.% and a
39
     viscosity of 2,000-10,000 (5,000-70,000) cps. Examples of
40
     (B) are styrene/maleic anhydride, isobutylene/maleic
41
     anhydride copolymers and alkali-soluble polyvinyl acetate
42
     emulsion. A suitable (A)/(B) wt. ratio is 100/4-10.
43
44
    USE/ADVANTAGE - The adhesive compsn. is suitable for
45
    labelling esp. plastic bottles. It exhibits the same level
46
    of initial adhesion and water-resistant adhesion as
47
     conventional emulsion type and solvent solution type
```

```
adhesives. When bottles are recycled, labels can be easily
    peeled off of the bottles. CHOSEN-DRAWING: Dwg.0/0
2
3
    TITLE-TERMS:
4
    ADHESIVE COMPOSITION LABEL RECYCLE BOTTLE COMPRISE EMULSION
5
    EVA POLY METHO ACRYLATE WATER INSOLUBLE COMPOUND SWELLING
6
    DISSOLVE ALKALI
7
8
    ADDL-INDEXING-TERMS:
9
    METHACRYLATE!
10
11
    DERWENT-CLASS: A18 A81 G03 P85
12
13
    CPI-CODES: A04-F06E6; A04-G07; A12-P; A12-W03; G03-B02D1;
14
15
    G03-B02D2;
16
    SECONDARY-ACC-NO:
17
    CPI Secondary Accession Numbers: C1993-141378
18
    Non-CPI Secondary Accession Numbers: N1993-244789
19
20
```